Fantasea Line
FML Lens Port Table

Help us improve our lens compatibility info and win $100 in Fantasea store credit!
For additional details, Please contact us at info@fantasea.com

Lens Name	Lens Use	Lens Gear	Lens Gear Function	Lens Port	Additional Info
Canon EF 8-15mm f/4L Fisheye USM Lens (4427B002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Wide (Zoom)	C55G Lens Gear Canon 8-15 Fisheye USM (#2253)	Zoom Gear (use auto focus)	FML- FNX Converter 55G (#2131) + Sea&Sea NX Compact Dome Port (#SS-56601) or FML- FNX Converter 55G (#2131) + Sea&Sea Optical Dome Port II 100	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).
Tokina 10-17 mm f/3.5-4.5 AT-X 107 AF DX Fisheye Lens for Canon (ATXAF107DXC) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Wide (Zoom)	C55G Tokina ATXAF107DXC Lens Gear (#2251)	Zoom Gear (use auto focus)	FML- FNX Converter 55G (#2131) + Sea&Sea NX Compact Dome Port (#SS-56601) or FML- FNX Converter 55G (#2131) + Sea&Sea Optical Dome Port II 100	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).
Canon EF-S 10-18mm f/4.5-5.6 IS STM Lens (9519B002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Wide (Zoom)	-	Set desired focal length ahead and use auto focus	FML Dome Port A6 (#2111) + FML Port Extension 25 (#2121) + FML Port Extension 25 (#2121)	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).
Sony E 10-18 mm f/4 OSS Lens (SEL1018)	Wide (Zoom)	SEL1018 Lens Gear (#2211)	Zoom Gear (use auto focus)	FML Dome Port A6 (#2111) + FML Port Extension 25 (#2121)	

Lens Name	Lens Use	Lens Gear	Lens Gear Function	Lens Port	Additional Info
Zeiss Touit 12mm f/2.8 Lens *with Sony E-Mount* (2030-526)	Wide	-	Use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea NX Compact Dome Port (#SS-56601)	
Sony FE 12-24mm f/4 G Lens (SEL1224G)	Wide (Zoom)	-	Set desired focal length ahead and use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea NX Compact Dome Port (#SS-56601)	
Sigma 16mm f/1.4 DC DN Contemporary Lens for Sony E(402965)	Wide	-	Use auto focus	FML Dome Port A6 (#2111) + FML Port Extension 25 (#2121)	
Sony E 16 mm f/2.8 Lens (SEL16F28)	Wide	-	Use auto focus	FML Dome Port A6 (#2111)	Requires Light Shielding Pad SEL16F28 (#2301)
Sony Sony E 16 mm f/2.8 Lens (SEL16F28) + Sony Fisheye Converter (VCL-ECF-1 or VCL-ECF-2)	Wide	-	Use auto focus	FML Dome Port A6 (#2111)	Requires Light Shielding Pad SEL16F28 (#2301)
Sony Sony E 16 mm f/2.8 Lens (SEL16F28) + Sony Ultra Wide Converter (VCL-ECU-1 or VCL-ECU-2)	Wide	-	Use auto focus	FML Dome Port A6 (#2111) + FML Port Extension 25 (#2121)	Requires Light Shielding Pad SEL16F28 (#2301)
Canon EF 16-35mm f/4L IS USM Lens (9518B002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Wide (Zoom)	-	Set desired focal length ahead and use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea Extension Ring 20L (#SS-30123) + Sea&Sea NX Compact Dome Port (#SS-56601)	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).
Canon EF 16-35mm f/2.8L III USM Lens (0573C002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Wide (Zoom)	-	Set desired focal length ahead and use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea Extension Ring 20L (#SS-30123) + Sea&Sea Extension Ring 30L (#SS-30124) + Sea&Sea NX Compact Dome Port (#SS-56601)	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).

Lens Name	Lens Use	Lens Gear	Lens Gear Function	Lens Port	Additional Info
Sony E PZ 16–50 mm f/3.5–5.6 OSS Lens (SELP1650)	Zoom	SELP1650 Lens Gear (#2201)	Focus and Zoom Gear	FML Flat Port 34 (#2101)	Port features a 67mm front thread
Sony 16-70 mm f/4 Vario Tessar T* E 16-70mm ZA OSS Lens (SEL1670Z)	Wide (Zoom)	-	Set desired focal length ahead and use auto focus	FML Dome Port A6 (#2111) + FML Port Extension 25 (#2121) + FML Port Extension 25 (#2121)	
Canon EF 17-40mm f/4L USM Lens (8806A002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Wide (Zoom)	-	Set desired focal length ahead and use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea NX Compact Dome Port (#SS-56601)	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).
Sony E 18-135mm f/3.5-5.6 OSS Lens (SEL18135)	Zoom	-	Set desired focal length ahead and use auto focus	FML Dome Port A6 (#2111) + FML Port Extension 25 (#2121)	
Sony E 30 mm f/3.5 Macro Lens (SEL30M35)	Macro	SEL30M35 Lens Gear (#2203)	Focus Gear	FML Flat Port 34 (#2101)	Port features a 67mm front thread
Sony FE 50 mm f/2.8 Macro Lens (SEL50M28)	Macro	-	Use auto focus	FML Flat Port 34 (#2101) + FML Port Extension 25 (#2121) + FML Port Extension 25 (#2121)	Port features a 67mm front thread
Canon EF-S 60mm f/2.8 Macro USM Lens (0284B002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Macro	-	Use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea DX Macro Port 52 (#SS-30111)	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light). Port features a 67mm front thread.
Sony FE 90 mm f/2.8 Macro G OSS Lens (SEL90M28G)	Macro	C55G SEL90M28G Lens Gear (#2261)	Focus Gear	FML- FNX Converter 55G (#2131) + Sea&Sea Extension Ring 20L (#SS-30123) + Sea&Sea DX Macro Port 52 (#SS-30111)	Port features a 67mm front thread. **This setup is NOT compatible with the FA6000 Housing.**

Lens Name	Lens Use	Lens Gear	Lens Gear Function	Lens Port	Additional Info
Canon EF 100mm f/2.8L Macro IS USM Lens (3554B002) + Metabones Canon EF/EF-S Lens to Sony E Mount Adapter (MB EF-E-BT5)	Macro	-	Use auto focus	FML- FNX Converter 55G (#2131) + Sea&Sea DX Macro Port 87 (#SS-30119)	Metabones Adapter requires dismounting adapter's tripod foot and for most setups, the recommended adapter mode is the *Green Mode* (blue light).